

# SAFETY DATA SHEET

## 1. Identification

**Product number** 1000013002  
**Product identifier** **10 OZ WEAVER WINNERS PRO ENHNCR LB 12PK**  
**Company information** WEAVER LEATHER LLC  
7540 CR 201  
MT HOPE, OH 44660 United States  
**Company phone** General Assistance 330-674-7548  
**Emergency telephone US** 1-800-255-3924  
**Emergency telephone outside US** 1-800-255-3924  
**Version #** 01  
**Recommended use** ADHESIVE  
**Recommended restrictions** None known.

## 2. Hazard(s) identification

**Physical hazards** Flammable aerosols Category 1  
**Health hazards** Acute toxicity, oral Category 4  
Acute toxicity, inhalation Category 3  
Skin corrosion/irritation Category 2  
Sensitization, skin Category 1  
Specific target organ toxicity, single exposure Category 3 narcotic effects  
Aspiration hazard Category 1  
**Environmental hazards** Hazardous to the aquatic environment, acute hazard Category 2  
Hazardous to the aquatic environment, long-term hazard Category 2  
**OSHA defined hazards** Not classified.

### Label elements



**Signal word** Danger  
**Hazard statement** Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness.  
**Precautionary statement**  
**Prevention** Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves.  
**Response** If swallowed: Immediately call a poison center/doctor. If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. Specific treatment (see this label). Do NOT induce vomiting. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.  
**Storage** Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.  
**Hazard(s) not otherwise classified (HNOC)** None known.

Supplemental information None.

### 3. Composition/information on ingredients

#### Mixtures

| Chemical name                                | Common name and synonyms | CAS number | %        |
|--|--------------------------|------------|----------|
| 2-Methylpentane                              |                          | 107-83-5   | 10 - 20  |
| Dimethyl Ether                               |                          | 115-10-6   | 10 - 20  |
| 1,1-Difluoroethane                           |                          | 75-37-6    | 2.5 - 10 |
| 2,2-Dimethylbutane                           |                          | 75-83-2    | 2.5 - 10 |
| 2,3-Dimethylbutane                           |                          | 79-29-8    | 2.5 - 10 |
| 3-Methylpentane                              |                          | 96-14-0    | 2.5 - 10 |
| Acetone                                      |                          | 67-64-1    | 2.5 - 10 |
| Butane                                       |                          | 106-97-8   | 2.5 - 10 |
| Cyclohexane                                  |                          | 110-82-7   | 2.5 - 10 |
| Hydrocarbons, C9-unsaturated,<br>Polymerized |                          | 71302-83-5 | 2.5 - 10 |
| Propane                                      |                          | 74-98-6    | 2.5 - 10 |
| Other components below reportable levels     |                          |            | 10 - 20  |

\*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

### 4. First-aid measures

|   |   |
|---|---|
| <b>Inhalation</b>   | Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.   |
| <b>Skin contact</b>   | Remove contaminated clothing. Wash off with soap and plenty of water. If skin irritation occurs: Get medical advice/attention.  |
| <b>Eye contact</b>  | Rinse with water. Get medical attention if irritation develops and persists.  |
| <b>Ingestion</b>  | Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Aspiration may cause pulmonary edema and pneumonitis. |
| <b>Most important symptoms/effects, acute and delayed</b>                     | Irritant effects. May cause drowsiness or dizziness.  |
| <b>Indication of immediate medical attention and special treatment needed</b> | Provide general supportive measures and treat symptomatically.  |
| <b>General information</b>  | Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. If you feel unwell, seek medical advice (show the label where possible). Wash contaminated clothing before reuse.      |

### 5. Fire-fighting measures

|  |   |
|--|---|
| <b>Suitable extinguishing media</b>                                  | Water. Foam. Dry powder. Carbon dioxide (CO <sub>2</sub> ).   |
| <b>Unsuitable extinguishing media</b>                                | None known.   |
| <b>Specific hazards arising from the chemical</b>                    | Contents under pressure. Pressurized container may explode when exposed to heat or flame.   |
| <b>Special protective equipment and precautions for firefighters</b> | Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.  |
| <b>Fire-fighting equipment/instructions</b>                          | Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. |
| <b>Specific methods</b>  | Use standard firefighting procedures and consider the hazards of other involved materials. Move container from fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. In the event of fire and/or explosion do not breathe fumes.                     |
| <b>General fire hazards</b>  | Extremely flammable aerosol.  |

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate personal protective equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

### Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Collect spillage. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.

### Environmental precautions

Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

### Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Ground and bond containers when transferring material. Do not re-use empty containers. Avoid breathing gas. Avoid contact with skin. Avoid contact with eyes. Avoid prolonged exposure. Use only in well-ventilated areas. Observe good industrial hygiene practices. Wash hands thoroughly after handling. Do not empty into drains.

### Conditions for safe storage, including any incompatibilities

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Refrigeration recommended. Store away from incompatible materials (see Section 10 of the SDS). Level 3 Aerosol.

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Components                 | Type | Value                  |
|----------------------------|------|------------------------|
| Acetone (CAS 67-64-1)      | PEL  | 2400 mg/m3<br>1000 ppm |
| Cyclohexane (CAS 110-82-7) | PEL  | 1050 mg/m3<br>300 ppm  |
| Propane (CAS 74-98-6)      | PEL  | 1800 mg/m3<br>1000 ppm |

#### US. ACGIH Threshold Limit Values

| Components                       | Type | Value    |
|----------------------------------|------|----------|
| 2,2-Dimethylbutane (CAS 75-83-2) | STEL | 1000 ppm |
| 2,3-Dimethylbutane (CAS 79-29-8) | TWA  | 500 ppm  |
|                                  | STEL | 1000 ppm |
| 2-Methylpentane (CAS 107-83-5)   | TWA  | 500 ppm  |
|                                  | STEL | 1000 ppm |
| 3-Methylpentane (CAS 96-14-0)    | TWA  | 500 ppm  |
|                                  | STEL | 1000 ppm |
| Acetone (CAS 67-64-1)            | TWA  | 500 ppm  |
|                                  | STEL | 750 ppm  |
| Butane (CAS 106-97-8)            | TWA  | 500 ppm  |
|                                  | STEL | 1000 ppm |
| Cyclohexane (CAS 110-82-7)       | TWA  | 100 ppm  |

**US. NIOSH: Pocket Guide to Chemical Hazards**

| Components                 | Type | Value                  |
|----------------------------|------|------------------------|
| Acetone (CAS 67-64-1)      | TWA  | 590 mg/m3<br>250 ppm   |
| Butane (CAS 106-97-8)      | TWA  | 1900 mg/m3<br>800 ppm  |
| Cyclohexane (CAS 110-82-7) | TWA  | 1050 mg/m3<br>300 ppm  |
| Propane (CAS 74-98-6)      | TWA  | 1800 mg/m3<br>1000 ppm |

**US. Workplace Environmental Exposure Level (WEEL) Guides**

| Components                       | Type | Value                  |
|----------------------------------|------|------------------------|
| 1,1-Difluoroethane (CAS 75-37-6) | TWA  | 2700 mg/m3<br>1000 ppm |
| Dimethyl Ether (CAS 115-10-6)    | TWA  | 1880 mg/m3<br>1000 ppm |

**Biological limit values****ACGIH Biological Exposure Indices**

| Components            | Value   | Determinant | Specimen | Sampling Time |
|-----------------------|---------|-------------|----------|---------------|
| Acetone (CAS 67-64-1) | 50 mg/l | Acetone     | Urine    | *             |

\* - For sampling details, please see the source document.

**Appropriate engineering controls**

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

Wear eye/face protection. Wear safety glasses with side shields (or goggles).

**Hand protection**

Wear protective gloves.

**Skin protection****Other**

Wear appropriate chemical resistant clothing.

**Respiratory protection**

If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

**Thermal hazards**

Wear appropriate thermal protective clothing, when necessary.

**General hygiene considerations**

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

**9. Physical and chemical properties****Appearance****Physical state**

Liquid.

**Form**

Aerosol.

**Color**

Not available.

**Odor**

Not available.

**Odor threshold**

Not available.

**pH**

Not available.

**Melting point/freezing point**

Not available.

**Initial boiling point and boiling range**

137.83 °F (58.79 °C) estimated

**Flash point**

-156.0 °F (-104.4 °C) estimated

**Evaporation rate**

Not available.

**Flammability (solid, gas)**

Not available.

## Upper/lower flammability or explosive limits

|                                |                  |
|--------------------------------|------------------|
| Flammability limit - lower (%) | 2.6 % estimated  |
| Flammability limit - upper (%) | 12.3 % estimated |
| Explosive limit - lower (%)    | Not available.   |
| Explosive limit - upper (%)    | Not available.   |

Vapor pressure 282.22 psig @70F estimated

Vapor density Not available.

Relative density 0.706 g/cm3 estimated

## Solubility(ies)

Solubility (water) Not available.

Partition coefficient (n-octanol/water) Not available.

Auto-ignition temperature 665.06 °F (351.7 °C) estimated

Decomposition temperature Not available.

Viscosity Not available.

## Other information

Density 0.71 g/cm3 estimated

Flammability class Flammable IB estimated

Heat of combustion 39.26 kJ/g estimated

Heat of combustion (NFPA 30B) 39.26 kJ/g estimated

Percent volatile 80.71 % estimated

Specific gravity 0.706 estimated

VOC (Weight %) 50.24 % estimated

## 10. Stability and reactivity

**Reactivity** The product is stable and non-reactive under normal conditions of use, storage and transport.

**Chemical stability** Material is stable under normal conditions.

**Possibility of hazardous reactions** Hazardous polymerization does not occur.

**Conditions to avoid** Avoid temperatures exceeding the flash point.

**Incompatible materials** Strong oxidizing agents. Fluorine. Chlorine. Nitrates.

**Hazardous decomposition products** No hazardous decomposition products are known.

## 11. Toxicological information

### Information on likely routes of exposure

**Ingestion** May be fatal if swallowed and enters airways.

**Inhalation** May be fatal if swallowed and enters airways. Prolonged inhalation may be harmful. Narcotic effects.

**Skin contact** Causes skin irritation.

**Eye contact** Direct contact with eyes may cause temporary irritation.

**Symptoms related to the physical, chemical and toxicological characteristics** Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Irritant effects.

### Information on toxicological effects

**Acute toxicity** May be fatal if swallowed and enters airways. Narcotic effects.

| Components   | Species    | Test Results   |
|--|------------|--|
| 1,1-Difluoroethane (CAS 75-37-6)                           |            |  |
| <b>Acute</b>   |            |  |
| <i>Inhalation</i>  |            |  |
| LC50   | Rat        | 44 - 437500 %, 4 Hours                               |
| Acetone (CAS 67-64-1)                                      |            |  |
| <b>Acute</b>   |            |  |
| <i>Dermal</i>  |            |  |
| LD50   | Guinea pig | > 7426 mg/kg, 24 Hours<br>> 9.4 ml/kg, 24 Hours      |
|  | Rabbit     | > 7426 mg/kg, 24 Hours<br>> 9.4 ml/kg, 24 Hours      |
| <i>Inhalation</i>  |            |  |
| LC50   | Rat        | 55700 ppm, 3 Hours<br>132 mg/l, 3 Hours<br>50.1 mg/l |
| <i>Oral</i>  |            |  |
| LD50   | Rat        | 5800 mg/kg<br>2.2 ml/kg                              |
| Butane (CAS 106-97-8)                                      |            |  |
| <b>Acute</b>   |            |  |
| <i>Inhalation</i>  |            |  |
| LC50   | Mouse      | 1237 mg/l, 120 Minutes<br>52 %, 120 Minutes          |
|  | Rat        | 1355 mg/l  |
| Cyclohexane (CAS 110-82-7)                                 |            |  |
| <b>Acute</b>   |            |  |
| <i>Dermal</i>  |            |  |
| LD50   | Rabbit     | > 2000 mg/kg   |
| <i>Inhalation</i>  |            |  |
| LC50   | Rat        | > 32880 mg/m3, 4 Hours<br>> 5540 ppm, 4 Hours        |
| Dimethyl Ether (CAS 115-10-6)                              |            |  |
| <b>Acute</b>   |            |  |
| <i>Inhalation</i>  |            |  |
| NOEL   | Rat        | 2 ppm, 6 Hours                                       |
| <i>Oral</i>  |            |  |
| LD50   | Rat        | 460 mg/kg  |
| Hydrocarbons, C9-unsaturated, Polymerized (CAS 71302-83-5) |            |  |
| <b>Acute</b>   |            |  |
| <i>Dermal</i>  |            |  |
| LD50   | Rat        | > 2000 mg/kg, 24 Hours                               |
| <i>Inhalation</i>  |            |  |
| LC50   | Rat        | > 5.14 mg/l, 4 Hours                                 |
| <i>Oral</i>  |            |  |
| LD50   | Rat        | > 16 ml/kg   |
| Propane (CAS 74-98-6)                                      |            |  |
| <b>Acute</b>   |            |  |
| <i>Inhalation</i>  |            |  |
| LC50   | Mouse      | 1237 mg/l, 120 Minutes                               |

| Components | Species | Test Results      |
|------------|---------|-------------------|
|            |         | 52 %, 120 Minutes |
|            | Rat     | 1355 mg/l         |
|            |         | 658 mg/l/4h       |

\* Estimates for product may be based on additional component data not shown.

|   |  |
|---|--|
| <b>Skin corrosion/irritation</b>                                      | Causes skin irritation.  |
| <b>Serious eye damage/eye irritation</b>                              | Direct contact with eyes may cause temporary irritation.   |
| <b>Respiratory or skin sensitization</b>                              |  |
| <b>Respiratory sensitization</b>                                      | Not available.   |
| <b>Skin sensitization</b>   | This product is not expected to cause skin sensitization.  |
| <b>Germ cell mutagenicity</b>   | No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic. |
| <b>Carcinogenicity</b>  | This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.                                  |
| <b>OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)</b> |  |
|   | Not listed.  |
| <b>Reproductive toxicity</b>  | This product is not expected to cause reproductive or developmental effects.                                     |
| <b>Specific target organ toxicity - single exposure</b>               | Narcotic effects.  |
| <b>Specific target organ toxicity - repeated exposure</b>             | Not classified.  |
| <b>Aspiration hazard</b>  | May be fatal if swallowed and enters airways.  |
| <b>Chronic effects</b>  | Prolonged inhalation may be harmful.   |

## 12. Ecological information

**Ecotoxicity** Toxic to aquatic life with long lasting effects. Accumulation in aquatic organisms is expected.

| Components                    | Species | Test Results  |
|-------------------------------|---------|---|
| Acetone (CAS 67-64-1)         |         |   |
| <b>Aquatic</b>                |         |   |
| Crustacea                     | EC50    | Water flea (Daphnia magna) 21.6 - 23.9 mg/l, 48 hours                           |
| Fish                          | LC50    | Rainbow trout, donaldson trout (Oncorhynchus mykiss) 4740 - 6330 mg/l, 96 hours |
| Cyclohexane (CAS 110-82-7)    |         |   |
| <b>Aquatic</b>                |         |   |
| Fish                          | LC50    | Fathead minnow (Pimephales promelas) 23.03 - 42.07 mg/l, 96 hours               |
| Dimethyl Ether (CAS 115-10-6) |         |   |
| <b>Aquatic</b>                |         |   |
| Crustacea                     | EC50    | Water flea (Daphnia pulex) 4.3 - 7.8 mg/l, 48 hours                             |
| Fish                          | LC50    | Striped bass (Morone saxatilis) 10.302 - 16.743 mg/l, 96 hours                  |

\* Estimates for product may be based on additional component data not shown.

**Persistence and degradability** No data is available on the degradability of this product.

**Bioaccumulative potential** No data available.

### Partition coefficient n-octanol / water (log Kow)

|                    |       |
|--------------------|-------|
| 1,1-Difluoroethane | 0.75  |
| 2,2-Dimethylbutane | 3.82  |
| 2,3-Dimethylbutane | 3.42  |
| 2-Methylpentane    | 3.74  |
| 3-Methylpentane    | 3.6   |
| Acetone            | -0.24 |
| Butane             | 2.89  |
| Cyclohexane        | 3.44  |
| Dimethyl Ether     | 0.1   |
| Propane            | 2.36  |

|                              |   |
|------------------------------|---|
| <b>Mobility in soil</b>      | No data available.  |
| <b>Other adverse effects</b> | No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component. |

### 13. Disposal considerations

|  |   |
|--|---|
| <b>Disposal instructions</b>                     | Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations. |
| <b>Local disposal regulations</b>                | Dispose in accordance with all applicable regulations.  |
| <b>Hazardous waste code</b>                      | The waste code should be assigned in discussion between the user, the producer and the waste disposal company.  |
| <b>US RCRA Hazardous Waste U List: Reference</b> |   |
| Acetone (CAS 67-64-1)                            | U002  |
| Cyclohexane (CAS 110-82-7)                       | U056  |
| <b>Waste from residues / unused products</b>     | Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).  |
| <b>Contaminated packaging</b>                    | Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.  |

### 14. Transport information

|   |   |
|---|---|
| <b>DOT</b>  |   |
| <b>UN number</b>  | UN1950  |
| <b>UN proper shipping name</b>  | Aerosols, flammable   |
| <b>Transport hazard class(es)</b>   |   |
| <b>Class</b>  | 2.1   |
| <b>Subsidiary risk</b>  | -   |
| <b>Label(s)</b>   | None  |
| <b>Packing group</b>  | Not applicable.   |
| <b>Special precautions for user</b>   | Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling. |
| <b>Special provisions</b>   | N82   |
| <b>Packaging exceptions</b>   | 306   |
| <b>Packaging non bulk</b>   | None  |
| <b>Packaging bulk</b>   | None  |
| This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently. |   |
| <b>IATA</b>   |   |
| <b>UN number</b>  | UN1950  |
| <b>UN proper shipping name</b>  | Aerosols, flammable   |
| <b>Transport hazard class(es)</b>   |   |
| <b>Class</b>  | 2.1   |
| <b>Subsidiary risk</b>  | -   |
| <b>Label(s)</b>   | 2.1   |
| <b>Packing group</b>  | Not applicable.   |
| <b>Environmental hazards</b>  | Yes   |
| <b>ERG Code</b>   | 10L   |
| <b>Special precautions for user</b>   | Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling. |
| <b>Other information</b>  |   |
| <b>Passenger and cargo aircraft</b>   | Allowed.  |
| <b>Cargo aircraft only</b>  | Allowed.  |
| <b>Packaging Exceptions</b>   | LTD QTY   |
| <b>IMDG</b>   |   |
| <b>UN number</b>  | UN1950  |







## US. Pennsylvania Worker and Community Right-to-Know Law

2,2-Dimethylbutane (CAS 75-83-2)  
2,3-Dimethylbutane (CAS 79-29-8)  
2-Methylpentane (CAS 107-83-5)  
3-Methylpentane (CAS 96-14-0)  
Acetone (CAS 67-64-1)  
Butane (CAS 106-97-8)  
Cyclohexane (CAS 110-82-7)  
Dimethyl Ether (CAS 115-10-6)  
Propane (CAS 74-98-6)

## US. Rhode Island RTK

1,1-Difluoroethane (CAS 75-37-6)  
Acetone (CAS 67-64-1)  
Butane (CAS 106-97-8)  
Cyclohexane (CAS 110-82-7)  
Dimethyl Ether (CAS 115-10-6)  
Propane (CAS 74-98-6)

## US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

### US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Ethyl Benzene (CAS 100-41-4)

Listed: June 11, 2004

## International Inventories

| Country(s) or region        | Inventory name   | On inventory (yes/no)* |
|-----------------------------|--|------------------------|
| Australia                   | Australian Inventory of Chemical Substances (AICS)                     | No                     |
| Canada                      | Domestic Substances List (DSL)   | Yes                    |
| Canada                      | Non-Domestic Substances List (NDSL)                                    | No                     |
| China                       | Inventory of Existing Chemical Substances in China (IECSC)             | No                     |
| Europe                      | European Inventory of Existing Commercial Chemical Substances (EINECS) | No                     |
| Europe                      | European List of Notified Chemical Substances (ELINCS)                 | No                     |
| Japan                       | Inventory of Existing and New Chemical Substances (ENCS)               | No                     |
| Korea                       | Existing Chemicals List (ECL)  | No                     |
| New Zealand                 | New Zealand Inventory  | No                     |
| Philippines                 | Philippine Inventory of Chemicals and Chemical Substances (PICCS)      | No                     |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory                          | Yes                    |

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

Issue date 09-15-2015

Version # 01

### Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.